

# **Material Safety Data Sheet**

The Dow Chemical Company

Product Name: ETHAFOAM\* 221 A/S Pink Polyethylene Foam Issue Date: 2007.06.26

Sheet

Print Date: 27 Jun 2007

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# 1. Product and Company Identification

#### **Product Name**

ETHAFOAM\* 221 A/S Pink Polyethylene Foam Sheet

## **COMPANY IDENTIFICATION**

The Dow Chemical Company 2030 Willard H. Dow Center Midland, MI 48674 USA

For MSDS updates and Product Information: 800-258-2436

Prepared By: Prepared for use in Canada by EH&S, Product Regulatory

Management Department.

450-652-1029

**Revision** 2007.06.26 **Print Date:** 6/27/2007

Customer Information Number: 800-258-2436

**EMERGENCY TELEPHONE NUMBER** 

**24-Hour Emergency Contact:** 989-636-4400 **Local Emergency Contact:** 519-339-3711

# 2. Hazards Identification

**Emergency Overview** 

Color: Pink

Physical State: Foam Odor: Odorless Hazards of product:

No significant immediate hazards for emergency response are known.

Sheet

#### **Potential Health Effects**

Eye Contact: Solid or dust may cause irritation or corneal injury due to mechanical action.

Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

**Skin Contact:** Prolonged contact may cause slight skin irritation with local redness.

Skin Absorption: Skin absorption is unlikely due to physical properties.

**Inhalation:** Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation.

Ingestion: Swallowing is unlikely because of the physical state. Very low toxicity if swallowed.

Harmful effects not anticipated from swallowing small amounts. May cause choking or blockage of the

digestive tract if swallowed.

# 3. Composition/information on ingredients

Component	CAS#	Amount W/W
Ethene, homopolymer	9002-88-4	> 95.0 %

Amounts are presented as percentages by weight.

# 4. First-aid measures

**Eye Contact:** Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.

Skin Contact: Wash skin with plenty of water.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Ingestion: If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give

laxatives. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient.

# 5. Fire Fighting Measures

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

**Unusual Fire and Explosion Hazards:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated.

See Section 9 for related Physical Properties

Sheet

## Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Recover spilled material if possible. See

Section 13, Disposal Considerations, for additional information.

Personal Precautions: There are no special required instructions.

Environmental Precautions: There are no special required instructions.

# 7. Handling and Storage

## Handling

**General Handling:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product is combustible and may constitute a fire hazard if improperly used or installed.

#### Storage

Store in a cool, dry place. Keep away from high temperatures and hot pipes. Store away from direct sunlight. This material is combustible and should not be exposed to flame or other ignition sources.

# 8. Exposure Controls / Personal Protection

## **Exposure Limits**

Consult local authorities for recommended exposure limits.

None established

### **Personal Protection**

**Eye/Face Protection:** Eye protection should not be necessary. For fabrication operations safety glasses are recommended. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

**Skin Protection:** Wear clean, body-covering clothing.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task. Examples of preferred glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. When respiratory protection is required for certain operations, including but not limited to saw, router or hotwire cutting, use an approved air-purifying respirator. In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

**Ingestion:** No precautions necessary due to the physical properties of the material.

#### **Engineering Controls**

**Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Sheet

#### 9. **Physical and Chemical Properties**

**Physical State** Foam Color Pink Odor Odorless

Flash Point - Closed Cup 340 °C Literature Flammable Limits In Air Lower: Not applicable **Upper**: Not applicable

350 °C Literature

**Autoignition Temperature** 

Not applicable **Vapor Pressure Boiling Point (760 mmHg)** Not applicable. Vapor Density (air = 1) Not applicable Specific Gravity (H2O = 1) Not applicable **Freezing Point** Not applicable **Melting Point** > 70 °C Literature Solubility in Water (by insoluble in water

weight)

На Not applicable Not applicable **Kinematic Viscosity** 

#### 10. Stability and Reactivity

### Stability/Instability

Thermally stable at typical use temperatures.

Conditions to Avoid: Avoid temperatures above 70°C (158°F) Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

Incompatible Materials: Avoid contact with: Strong oxidizers.

### **Hazardous Polymerization**

Will not occur.

#### **Thermal Decomposition**

Decomposition products depend upon temperature, air supply and the presence of other materials.

#### 11. **Toxicological Information**

#### Repeated Dose Toxicity

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### 12. **Ecological Information**

**CHEMICAL FATE** 

## **Movement & Partitioning**

No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material is expected to float.

Sheet

## Persistence and Degradability

Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

#### **ECOTOXICITY**

Not expected to be acutely toxic to aquatic organisms.

# 13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Landfill. Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

# 14. Transport Information

#### **TDG Small container**

**NOT REGULATED** 

### TDG Large container

**NOT REGULATED** 

#### **IMDG**

**NOT REGULATED** 

#### ICAO/IATA

**NOT REGULATED** 

# 15. Regulatory Information

#### **US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

### **CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

# **Hazardous Products Act Information: CPR Compliance**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### Hazardous Products Act Information: WHMIS Classification

This product is not a "Controlled Product" under WHMIS.

Sheet

# 16. Other Information

**Hazard Rating System** 

NFPA Health Fire Reactivity
0 1 0

#### **Recommended Uses and Restrictions**

Cushion packaging. Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group.

#### Revision

Identification Number: 80168 / 1001 / Issue Date 2007.06.26 / Version: 3.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
VOL/VOL	Volume/Volume

The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.